	Σh	nis specification app	lies to 12V POWER Cable, Model: WH-V0408-	500.							
	Gene	neral Specification									
ŀ	<u>_</u>	ltem	Specification N	Measurement condition, etc.							
l	Environ ment	Operation temp.	0 to 70℃ T	Temp. gradient 15℃/H							
		Storage temp.	-25 to 70℃ T	Temp. gradient 1·5℃/H							
L		Relative humidity	10 to 95%	No condensation							
	Others	Warranty	to us, the defective unit shall be repaired B	Expect any defects caused By the operation out of the specification.							
	Rated current, shape, dimension, etc.	Power supply Side  12 V -	<del>-</del> 500±15	Equipment Side							
		12V-1 CONNECTOR TYPE  Housing: 5557-08R (Mol Terminal: 5556 (Molex) or equivale:	PIN PIN MAX FUNCTION WIRE COLOR TYF  2 1 5.6A COM BLACK 1 2 5.6A COM BLACK 6 3 5.6A +12V YELLOW 5 4 5.6A +12V YELLOW 3 — — N.C. 4 — — N.C. 4 — — N.C.	Housing: 5557-04R (Molex)							
	Note	About Packaging Output wire harness shall be packed in plastic bag with model name label, and packed in a box separately with power supply unit.  (18, 8, 07) 株子プロン技術管理									

h ل		ked	(葬)	ved	_	Model name	Document No.	
Drawn	Yodo	Chec by	番	Approve by	=	WH-V0408-500	2785-03-4-520 1/1	۱

Nipron Co., Ltd.